

Texas

Bruno
9180



Coke
9475



Hazel
9051



Java
9811



Application:

Upholstery faux suede suitable for soft and restaurant style seating

Composition:

100% Polyester

Width:

145 cms + 2% usable

Weight:

310 gms/m²

Abrasion:

BS EN ISO 5470-2 : 2003 Method 1 > 50,000 Rubs

Flame Retardancy:

BS EN 1021 – 1: 2006 (Cigarette)

BS EN 1021 – 2 (Match)

BS 7176: 2007 Low Hazard

BS 7176: 2007 Medium Hazard

BS 5852: Section 4 Ignition Source 5

Note: FR back coating is applied top achieve FR levels.

Note: Flammability performance is dependent on foam used.

Tensile Strength:

BS EN ISO 13934-1 : 1999

Lengthway 1000N, Widthway 700N

Tear Resistance:

BS EN ISO 13927-2 : 2000

Warp 76N, Weft 64N

Light Fastness:

BS EN ISO 105 – BO2 : Method 3 to Standard – 4

Fastness to Rubbing:

BS EN ISO – X12 : 2002

Wet & Dry:

4 (Wet & Dry)

Colour Matching:

Batch to batch variations in shade may occur within commercial tolerances. We recommend that fabric be examined before use as no claims will be considered after cutting.

Availability:

Generally ex stock

Product Development:

We reserve the right to change the specification of our products in line with our product development program without notice.

Fabric Care and Maintenance:

Remove any spillages or stains with a damp cloth. Please refer to our cleaning and maintenance guide for additional details.

Technical Assistance:

Our Technical staff will be pleased to offer advice on F.R. and all other technical matters.